BRAICONE TO CB-30





The CB-30 centrifugal barrel finisher features highefficiency, a wide speed range, ease of operation and low noise levels all in an attractive machine enclosure. Revolving barrel groups rotate in opposite directions on independent axis driven by the planetary drive system. Media and working parts are worked under dual centrifugal forces which create an efficient and uniform chamfer, debur or polishing action.



STEEL COVER AND SLIDING DOOR WITH SAFETY LOCK

The steel plate machine cover features dual left and right side shutters, and a front sliding door equipped with a safety lock for safe operation and safe and convenient loading and unloading of parts and media.

MOTOR, MEDIA TROUGH AND ROTARY BARREL ASSEMBLY

The motor base is mounted on an adjustable bolt and can be moved up or down to adjust the tightness of the the motor belt. A media trough in the center of the unit facilitates loading (pouring) of the media, water and work parts mixture into the machine barrels. The rotary barrel plate assembly is composed of a belt assembly, chief axis, gear, chain assembly and fixed four-barrel group. The inner cartridge polyurethane barrels can be replaced when they become worn out.

CONTROL PANEL AND ELECTRICAL SYSTEM

The CB-30 is equipped with a world-class Inverter for precision speed adjustment to match the specific requirements needed for various working parts. Barrel angle can be adjusted by push-buttons on the control panel. The machine is also equipped with an AC electromagnetic brake, a hand brake, and a two-way ON/OFF switch for safe operation.

FOR PRICING Contact Vibra Finish Company.

MODEL CB-30*	
Barrel Speed (r/min)	0-180
Motor (KW)	1.5
Barrel Capacity (L)	4*7.5
Dimensions (mm)	1150*1000*1200
Weight (Kg)	500
Maximum Load (Kg)	17

^{*} OTHER SIZE UNITS AVAILABLE—CONTACT VIBRA FINISH COMPANY.





VIBRA FINISH CO. WARRANTY

The Seller warrants its equipment for a period of one (1) year from the date of shipment, or two thousand hours of operation, whichever occurs first, against defects in material and workmanship, unless otherwise specified in writing by the Seller, and has the right to replace any product proving defective. This warranty does not apply to common wear items such as belts, hoses, submersible compound pumps, etc. The Seller guarantees recommended processes and production rates only to the extent that they are established and authorized in writing by Seller's Customer Service Department. The Seller's obligation under this warranty is limited to the repair or replacement at the Seller's factory of any machinery part or parts thereof which shall be returned to the Seller with transportation charges prepaid, and which Seller's examination discloses, to its satisfaction, to have been defective. The warranty shall not apply to any equipment, which has been subject to misuse, negligence, accident, improper installation, unauthorized repair, or failure on the part of the Buyer to follow Seller's maintenance specifications. This Agreement contains the entire understanding of the parties concerning the goods purchased and supersedes all quotations, agreements, conversations, understandings, or contrary terms of purchase.

THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. THE SELLER DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, OF MERCHANTABILITY OF THE GOODS OR OF THE FITNESS OF THE GOODS FOR ANY PURPOSE BEYOND THOSE STATED ABOVE.



Vibra Finish Company •

WEST &&&\$B'G\U}UK U7California 9' \$*) Tel (8\$) 1) +, -0033 Fax (8\$) 1) +, -\$\$(& Toll Free 800-635-0259 www.vibrafinish.com EAST
84%Seward Road Hamilton, Ohio 45011
Tel (513) 870-6300
Fax (513) 870-6311
Toll Free 800-253-1941
www.vibrafinish.com