ADAPTIX™
Technical Specifications

- **Summary:** The Bullard Adaptix Type II Safety Helmet, Vented and Non Vented, is an advanced safety helmet that delivers both top and side impact protection with a sleek, balanced design. Engineered for all-day wear, it offers breathable comfort, customizable style, and advanced safety options to meet the demands of any job.

Specific Features:

- FlexBrim™ removable brim converts the Safety Helmet to a Full Brim Safety Helmet in seconds
- 10 helmet and 10 brim colors, available to mix and match; white, yellow, orange, red, black, dove gray, forest green, Kentucky blue, hi-viz orange, hi-viz yellow
- Ratchet suspension - Fits head sizes 6¼–8 (50-64cm)
- Mesh crown support can be adjusted to create up to ¾" clearance between head and crown foam
- Rear headband can be adjusted downward up to 1.4" (does not affect ride height)
- Comfort-fit, adjustable Berry-compliant chinstrap with 4-points of connection minimizes irritation and snag risk
- Breathable mesh crown support reduces pressure points and heat build up
- Accessory Compatibility. Integrated slots securely support hearing protection (coming soon), sunshades, and neck shades (compatible with most brands). Other compatible accessories include lights (band and adhesive mounted), face visors, and retractable eye protection (coming soon).
- 3-year limited warranty
- Customizable striping and logos using www.BuildYourBullard.com online configurator
- Bright, long-lasting logo printing available in 4 helmet locations
- HT - Higher temperature and LT - Lower temperature certified
- ANSI/ISEA Classification: Z89.1 Type II, Class E & G, Non Vented
- ANSI/ISEA Classification: Z89.1 Type II, Class C, Vented
- Declaration of Conformity – Level 3, Third Party Testing

ADAPTIX™
Technical Specifications

Bullard Adaptix Type II Safety Helmet Specifications

General

Weight:
- Without FlexBrim
  18.9 oz
- With FlexBrim
  21.9 oz

ANSI/ISEA Z89.1 Type II, Class E & G (Non-Vented)
ANSI/ISEA Z89.1 Type II, Class C (Vented)
Identifying Marks: Inverted 3 Ribs
Warning Labels: Yes
Decorating Capability: Yes -www.BuildYourBullard.com
Instructions with Unit: Yes
Helmet Shell Colors: 10
FlexBrim Colors: 10

Outer Shell

Shell Material: High-Density Polyethylene (HDPE)
FlexBrim Material: Thermoplastic Vulcanizate (TPV)
Style: Safety Helmet with FlexBrim Option
Accessory Slots: Yes
Adjustable Chin Strap
Rain Trough: No
Dimensions:
- With FlexBrim
  13.5” x 11”x 6.8” tall
- Without FlexBrim
  11”x 8.5”x 6.5” tall
- FlexBrim
  13.5”x 11”x 1.7” tall

Suspension

Type: FlexGen™ Ratchet

	Ratchet
Headband Sizes:	6 1/4 - 8 (50-64 cm)
Sizing Location:	Rear
Incremental Sizing:	Continuous Ratchet
# Vertical Adjustments:	5 Positions In The Rear
Crown Strap Material:	Nylon
Crown Strap Width:	20mm (.787") (2cm)
Color of Crown Straps:	Black
Brow Pad Material:	Polyester
Replaceable Brow Pad:	Yes

Bullard Center
2421 Fortune Drive
Lexington, KY 40509 • USA
877-BULLARD (285-5273)
Tel: +1-859-234-6616
Fax: +1-859-246-0243

Americas Operations
1898 Safety Way
Cynthiana, KY 41031 • USA
877-BULLARD (285-5273)
Tel: +1-859-234-6616
Fax: +1-859-234-8987

Bullard GmbH
Dieselstrasse 8a
53424 Remagen • Germany
Tel: +49-2642 999980
Fax: +49-2642 9999829

Bullard Asia Pacific Pte. Ltd.
51 Changi Business Park
Central 2
#03-04 The Signature
Singapore 486066
Tel: +65 6745 0556

©2026 Bullard. All rights reserved.
8350 (0326)

www.bullard.com